TACENS Gelus EXTREME



12dB

12cm FAN

FULL COPPER

SILENT OVERCLOCKING

- **POWERFUL BUT SILENT TACENS AURA PRO FAN WITH FLUXUS PRO BEARING AND ANTIVIBRATION PADS**
- **MANUAL SPEED CONTROL ON PCI FOR TOTAL USER FAN CONTROL FROM ULTRA-SILENT TO POWERFUL OVERCLOCKING COOLING**
- **POWERFUL SUPERCONDUCTOR HEATPIPE TECHNOLOGY**
- **FULL COPPER COOLER FOR EXTREME PERFORMANCE**
- **CHIPSET AND MEMORY COOLING THANKS TO ITS VERTICAL AIRFLOW SYSTEM**
- **HIGHEST PERFORMANCE LEVEL FOR SILENT OVERCLOCKING**
- **FAST AND EASY INSTALLATION FOR LGA775, AMD K8 & AM2**

INTEL LGA775
AMD K8
(754, 939 & 940)
AMD AM2
DUAL/QUAD CORE
COMPATIBLE

HEATSINK SPECIFICATIONS	
DIMENSIONS (mm)	145(L) x 120(W) x 82(H)
WEIGHT	434g
MATERIAL	FULL COPPER
SOCKET TYPE	INTEL LGA 775, AMD 754,930 & 940 AND AMD AM2
FAN SPECIFICATIONS	
DIMENSIONS (mm)	120 x 120 x 25 mm
WEIGHT	125g (170g WITH PCI FAN CONTROL)
FAN SPEED	1000 – 1800 R.P.M.
FAN AIRFLOW	53.3 – 77.5 CFM
LIFE EXPECTANCY	MORE THAN 60000 hrs
BEARING	TACENS FLUXUS PRO BEARING
VOLTAGE RATING	12V
NOISE LEVEL	12 – 21 dB

NEW TACENS FLUXUS PRO BEARING

ULTRA SILENT

LOWER NOISE THAN SLEEVE OR BALL BEARINGS

DUST PROOF DESIGN

CLOSED CONSTRUCTION PREVENT THE DUST AND FOREIGN BODY INTO DE BEARING

LONG LIFE

MORE THAN 60000 hrs

LOW WORKING TEMPERATURE

THE FAN WORKS PERFECTLY IN VERY HOT CONDITIONS

RoHS 2002/95/EG

ENVIRONMENTALY FRIENDLY

WWW.TACENS.COM **DESIGNED IN EUROPE**